# 31 PELTOR

3M<sup>™</sup> Hearing Solutions

## 3M<sup>™</sup> PELTOR<sup>™</sup> Wireless Communication Accessory

designed for 3M<sup>™</sup> X∕Series Earmuffs



3M Science. Applied to Life.™

MANUFACTURING MACHINERY: 93 dBA ....

## Communicate clearly without risking your hearing.

::::

Make and receive important calls without removing your hearing protection or leaving the noisy job site. Communicate with other crew members at the push of a button. With the 3M<sup>™</sup> PELTOR<sup>™</sup> Wireless Communication Accessory, you're always connected, so you can get updates, schedule meetings, track deliveries and more. MACHINE 2 REQUIRES MAINTENANCE

## Protected meets connected.

Everyone knows the importance of hearing protection on the job site. But removing hearing protection to communicate in loud environments can jeopardize your safety. Make the smart choice and protect your hearing without sacrificing communication with the 3M<sup>™</sup> PELTOR<sup>™</sup> Wireless Communication Accessory. It instantly turns your 3M<sup>™</sup> PELTOR<sup>™</sup> X Series Earmuffs into a wireless communications device for use in noisy environments. That's hearing protection and hands-free communication without compromise --that's how X Series works smarter.

Bluetooth<sup>®</sup> wireless technology Noise-cancelling microphone



- Assembles in seconds
- ▶ 8 hours talk/streaming time
- Resistant to harsh environmental elements (IP54)
- One-button operation

Simply remove ear cushion and snap into place.\*



#### 3M<sup>™</sup> Hearing Solutions

#### 3M<sup>™</sup> PELTOR<sup>™</sup> Wireless Communication Accessory

designed for 3M<sup>™</sup> X Series Earmuffs

#### **Ordering information**

Product	3M SAP ID	Product Description	Case Qty	
WS-CUSH	7100143063	3M <sup>™</sup> PELTOR <sup>™</sup> Wireless Communication Accessory designed for X Series Earmuffs	10 EA	
Technica	Technical Specifications			
Talk/streaming time: Approx. 8 hours				
<b>0</b> , <b>1</b> , <b>1</b>				

Standby time: Approx. 250 hours

Charge time: Approx. 3 hours

Operating temperature range: -20°C (-4°F) to 55°C (131°F)

Storage temperature range: -20°C(-4°F ) to 35°C (95°F)

Weight of the accessory: 55 g (1.94 oz)

Note: Hearing protector limits the entertainment audio signal to 82 dBA effective to the ear.



#### Works with most 3M<sup>™</sup> PELTOR<sup>™</sup> X Series Earmuffs



Also available for Hard Hat Attached X1P5E-X5P5E Earmuffs



Personal Safety Division

3M Canada P.O. Box 5757 London, Ontario N6A 4T1

1-800-267-4414 3M.ca/Hearing

### Find tools and resources for your hearing conservation program at 3M.ca/TownSquare.

The Bluetooth<sup>®</sup> word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by 3M is under license.

3M, Peltor and 3M Science. Applied to Life. are trademarks of 3M Used under license in Canada. © 2018, 3M. All rights reserved. 1802-11259 E BA-18-25724

#### **A**WARNING

#### Hearing Protection Products\*

These hearing protectors help reduce exposure to hazardous noise and other loud sounds. Misuse or failure to wear hearing protectors at all times that you are exposed to noise may result in hearing loss or injury. For proper use, see supervisor, User Instructions, or call 3M Technical Service at 1-800-267-4414. If there is any drainage from your ear or you have an ear infection, consult with your physician before wearing earplugs. Failure to do so may result in hearing loss or injury.