ESSENTIAL HARNESSC/W QUICK RELEASE PADDED BUCKLES

PART CODE: H101QR



- Pebble Weave Webbing design provides maximum grip for buckles, eliminating webbing slippage and the need for continual re-adjustment.
- High Tenacity UV stabilised webbing, enhances resistance to solvents and UV light degradation.
- Retro-Reflective Thread in webbing for improved visibility in low light.
- Rear Barr D allows easier access and better weight distribution for twin retractable fall arrest devices.
- Closed Loop Webbing system on rear Dorsal D maintains positioning of Dorsal D in the event of a fall. Significantly reducing the risk of injury from hardware hitting the back of workers head.
- Extended Belay Loops make connection of hardware easier, also maintains absolute front and centre positioning.
- Sub Pelvic Strap integration along the line of Belay Loops, places the worker away from hardware in the event of a fall, significantly reducing the risk of injury from hardware hitting the worker
- Articulated Chest Strap and shoulder adjustment points, designed for additional user comfort and female users, due to lower positioning of strap.
- · Quick Release Buckles. Padding under buckles.
- · Confined Space Rescue Loops.
- · Service Pouch on back.

APPLICATIONS >

Fall Arrest, Construction, Ladder, Scaffolding, Warehouse.

STANDARDS









Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.

SAFETY







GNANGARA, WA 6077
TECH SUPPORT: 1300 546 747
CUSTOMER SERVICE: 1300 770 723
EMAIL: INFO@PARAMOUNTSAFETY.COM



ESSENTIAL HARNESSC/W QUICK RELEASE PADDED BUCKLES

PART CODE: H101QR

HEIGHT SAFETY

PRODUCT DETAILS >

- · AUS/NZ designed and engineered
- · Size ranges available Small, Standard (M-L) and Maxi (XL-2XL)
- · 10-year life span from date of manufacture



DORSAL D RING



QUICK RELEASE





FRONT FALL ARREST ATTACHMENT POINTS



PADDING UNDER BUCKLES



CONFINED SPACE SPREADER BAR ATTACHMENT POINTS



RETRO REFLECTIVE THREAD

TECHNICAL INFORMATION >

- Webbing Material: Polyester; 45mm; UV Resilient
- Fall Arrest Hardware: Drop Forged corrosion resistant electrophoresis; high tensile steel
- Thread: Polyester; 9.81 Newtons (10kg) extension at break 19.5%
- Stitch Pattern: THETA Pattern combines 313 stitches to exceed 28kN of strength; AS/NZ compliant colour contrast
- Plastic Material: UV stabilised high-density polyethylene
- Weight: 1.4kg
- · Web Tenacity: 28kN
- Drop Forged D Rings: Alloy Steel; 40kN
- Buckle Strength: 12 to 17kN. Laser etched or hard marked on buckle
- Padding Material: Neoprene laminate









LINQ TEST LAB FACILITY

Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.



12 FELLOWSHIP ROAD, GNANGARA, WA 6077 TEUSTONER SUPPORT: 1300 546 747 CUSTOMER SERVICE: 1300 770 723 EMAIL: INFO@PARAMOUNTSAFETY.COM