

HURRICANE

TOUGH AND MODERN



1662201 • Clear



1662202 • Smoke



1662203 • Silver Flash



1662204 • Blue Flash



1662215 • Polarised



1662214 • Black Frame
Light Smoke Silver Flash Lens



1662209 • Bronze Frame
Silver Flash Lens



1662207 • Blue Frame
Blue Flash Lens



26 g

- + LIGHTWEIGHT, CONTOURED FRAME**
- + VELVET FINISH OVER HYDRATED NYLON FRAME**
- + POLARISED LENS TO ELIMINATE GLARE AND REDUCE EYE FATIGUE**
- + ANTI-FOG / ANTI-SCRATCH COATING**
- + FIT: MEDIUM/LARGE**

bolle
SAFETY

HURRICANE

TOUGH AND MODERN

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
HURRICANE	 Clear	1662201	I0	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Smoke	1662202	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Silver Flash Lens / Black Frame	1662203	I3	AS/NZS 1337.1.2010	Hard coat
	 Silver Flash Lens / Bronze Frame	1662209	I3	AS/NZS 1337.1.2010	Hard coat
	 Blue Flash Lens / Black Frame	1662204	I3	AS/NZS 1337.1.2010	Hard coat
	 Blue Flash Lens / Blue Frame	1662207	I3	AS/NZS 1337.1.2010	Hard coat
	 Light Smoke Silver Flash Lens	1662214	I3	AS/NZS 1337.1.2010	Hard coat
	 Green Polarised	1662215	I3	AS/NZS 1337.1.2010	Hard coat

LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).
- 3. Range of luminous transmittance 8-18% (smoke, flash & polarised).

APPLICATIONS

- Assembly and production work
- Process work
- Emergency response
- Driving
- Solar UV exposure
- Laboratory

MAIN MARKETS

- Manufacturing
- Petrochemical
- Construction
- Government
- Mining
- Medical and dental
- Food industry

LENSES

- 2.2mm polycarbonate
- 8 base curve
- Anti-fog/anti-scratch coating on both sides of lens: Clear and Smoke
- Hard coating on Silver and Blue Flash & Polarised lenses
- 99.9% UV 385 – Clear
- 99.9% UV 400 – Smoke, Silver Flash, Blue Flash and Polarised

FRAME MARKING

AS/NZS 1337.1:2010 Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6 mm ball at 45 m/s.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 8
FRAME	Hydrated Nylon
TEMPLES	Hydrated Nylon
STRAP	Non Applicable
FOAM	Non Applicable
SPARE LENSES	No

Non-contractual pictures

10/04/2020

Bollé Safety AU Pty Limited
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: sales@bollesafety.com.au

Hong Kong Bollé Safety
818, 8/F, Ocean Centre, Harbour City,
5 Canton Road, Tsim Sha Tsui,
Kowloon, Hong Kong
T.: +852 2732 5038

bollesafety.com.au

bolle
SAFETY